

GPS-FC-3T-BAS™

Compact Needlepoint Bipolar Ionization System Modified for High Voltage Input





Product Description

The compact GPS-FC-3T-BAS fits where traditional air cleaners don't, including fan coils, heat pump PTACs, ductless mini splits, ceiling cassettes, ducted modules, as well as traditional split systems and air handlers up to 3,200 CFM or 8 tons. The included APV-12-24 converts input voltages of 110-240VAC to 24VAC, making the GPS-FC-3T-BAS compatible with higher voltage systems.

Standard Features

Carbon Fiber Brushes, LED Operation Status, Integral BAS Alarm Contacts, Mounting Tabs, Positive and Negative Ion Output, 110-240V step-down power supply.

Benefits

-  Particle Reduction and Smoke Control
-  Odors Neutralized by destroying VOCs
-  Pathogens Killed (Bacteria, Viruses, Mold), Helps to Control Allergens/ Asthma*, Prevents Dirty Sock Syndrome
-  Energy Savings of 30% by Reducing Outdoor Air Intake by up to 75%, reduces pressure loss by keeping coils clean without expensive UV system, and requires No Maintenance!

*These statements are based on numerous customer testimonials and have not been evaluated by the FDA


Specifications

Input Voltage	110 - 240 VAC to the power supply
Power	12 Watts to the GPS-FC-3T-BAS
Frequency	50/60HZ
Total Ion Output	>350M ions/cc/sec
Airflow Capacity	0 - 3,200 CFM
Temperature/Humidity	-20° to 160°F / 0 - 100%
Unit Dimensions/Weight	2.6"L x 1.9"H x 1.3"D / 0.5 lbs
Electric Approvals	UL, CE
Compliance & Certifications	UL 867, OSHPD Seismic (OSP), IAQP
BAS Alarm Contact Rating	"Dry" Contact Type - 3A/115V Maximum



Commercial Applications

- Schools and Universities
- Arenas and Stadiums
- Transportation Hubs
- Office Buildings
- Manufacturing
- Food Service
- Animal Care
- Institutional
- Senior Care
- Healthcare
- Hospitality
- Child Care
- Worship
- Theatre



Engineering Air for a Cleaner World™

Global Plasma Solutions, Inc.
www.GlobalPlasmaSolutions.com